

easyScreen

The name says it all

Our new combined ABR + OAE newborn hearing screener

Exceed your NHS program goals

With our new easyScreen we unite ABR, TEOAE and DPOAE screening capabilities in one device to meet your need for a cost-efficient 2-step OAE/ABR screening system. Designed to lighten your daily workload easyScreen is portable and fits right into your pocket. Benefit from easyScreen's binaural automated ABR method and simply test not only one but both ears without losing any time.

Powerful ABR test method

Our unique CE-Chirp stimulus and powerful response detection algorithm work together to achieve accurate pass and refer results within seconds. The patented CE-Chirp® stimulates all regions of the cochlea at the same time and thus generates a much larger response – for faster results than a standard click.

Hearing screening made easy

Thanks to our user-friendly design, it is as easy to operate as a smartphone. The resistive 4.3" touchscreen works with medical gloves and allows the user to start a test with as few as 3 clicks. Feel more confident with our on-screen user guidance and overcome the challenges of newborn hearing screening with ease. Finally, print your test results instantly using the easyScreen wireless printer.

Improve your workflow

Simply place the base unit into the cradle to charge easyScreen. Store, view and manage patient and screening data with our dedicated HearSIM™ software – it is just as intuitive as handling easyScreen.

Features at a glance

- Fast and easy ABR + OAE hearing screening
- Powerful ABR detection algorithm for testing within seconds
- Truly intuitive user interface
- On-screen guidance; i.e. probe fitting feedback, noise monitoring
- Small and lightweight
- Large color touchscreen for comfortable navigation
- Very short boot-up time and long battery life
- Cradle for wireless charging
- HearSIM™ patient database and device manager

Upgradable to easyScreen BERAphone in 2018

 CE-Chirp® inside



Technical Data easyScreen

ABR

Stimuli	CE-Chirp®
Stimulus rate	~90 /s
Test mode	monaural or binaural
Level	35 dB nHL
Impedance test	Automatic pre-test
Test duration	10 s to 180 s
Artifact rejection level	100 µV
Transducer	IP30 with eartips or EarCups

TEOAE*

Stimulus type	Click
Level	83 dB SPL (in-ear calibration)
Analysis bands	1.4, 2, 2.8 and 4 kHz (center frequencies)
Pass criteria	3 out of 4 bands, min 6 dB SNR, min -5 dB SPL OAE level
Test duration	4 s to 60 s
Transducer	OAE Probe (50 or 120 cm cable length)

DPOAE*

Stimulus type	Pairs of pure tones
Level (L1/L2)	65/55 dB SPL
F2 Frequencies	2, 3, 4 and 5 kHz
F2/f1 ratio	1,22
Pass criteria	3 out of 4 bands, min 6 dB SNR, min -5 dB SPL OAE level
Test duration	4 s to 60 s
Transducer	OAE Probe (50 or 120 cm cable length)

SANIBEL

We recommend using only Sanibel disposables to guarantee optimal results.

Sanibel™

PREAMPLIFIER

One Channel	3 electrode cables (black, yellow and white)
Gain	72 dB
CMR Ratio	>110 dB at 100 Hz
Dimensions / Weight	85 x 50 x 25 mm / 85 g

easyScreen

Dimensions / Weight	163 x 85 x 21 mm / 265 g
Display	4.3" color touch screen
Languages	English, German, Spanish, French and more to come
Storage	max. 250 patients with 50 tests each
PC interface	micro USB
Battery	Rechargeable Li-ion

CRADLE

Charging	Wireless (inductive charging)
Power supply	5 V DC (micro USB)
Dimensions / Weight	142 x 140 x 62 mm / 270 g

STANDARDS

IEC 60645-6 2009 Type 2, IEC 60645-7 2009 Type 2, IEC 60601-1 Type B and BF, IEC 60601-1-2, according to the class IIa of the EU medical directive 93/42/EEC



STANDARD COMPONENTS

easyScreen, charging cradle, power supply, USB cable, preamplifier, transducer (IP30 and OAE probe*), electrode lead wires, carrying case, starter kit, cleaning cloth, stylus, neckstrap, HearSIM™ PC software

OPTIONAL COMPONENTS

Label printer

Standard Components



easyScreen device



Cradle



Preamplifier



Insert earphones



OAE probe*



Sanibel eartip starter kit

Optional Accessories



Wireless label printer

*only available in combination with ABR
Specifications are subject to change without notice.

MAICO Diagnostics GmbH

Sickingenstr. 70-71 · 10553 Berlin · Germany
Tel.: +49 30/70 71 46-50 · Fax: +49 30/70 71 46-99
sales@maico.biz · www.maico.biz